



SX shown with Pearl shell



SX shown with Pearl shell, Coastal Gray cabinet and Polymer step

Seating Capacity	3 adults
Dimensions	6' x 6' x 33"/1.83m x 1.83m x .84m
Water Capacity	285 gallons/1,075 liters
Weight	720 lbs./325 kg dry; 3,620 lbs./1,640 kg filled*
Spa Shell Options	Pearl or Desert
Cabinet Options	Coastal Gray, Espresso or Teak
Jets - 17	1 Moto-Massage° jet 16 Directional Precision° jets
Waterfall	n/a
Jet Pump 1	Wavemaster® 6200; Two-speed 1.5 HP Continuous Duty, 3.2 HP Breakdown Torque
Jet Pump 2	n/a
Circulation Pump (Optional)	SilentFlo 5000°
Water Care System	FROG [®] In-Line Cartridge Ready
Ozone System (Optional)	FreshWater® III Corona Discharge
Control System	IQ 2020° 115v/20 amp** (Includes G.F.C.I. protected power cord) or 115v/30amp*** or 220v/50amp***, 60Hz
Lighting	Blue LED light, dimmable; Splendors® multi-colored LED light, dimmable (optional)
Heater	No-Fault® 1000w/115v
Energy Efficiency	FiberCor® Insulation; Certified to the APSP 14 National Standard and the California Energy Commission (CEC) in accordance with California law
Effective Filtration Area	30 sq. ft., top loading
Vinyl Cover	3" to 2" tapered, 1 lb. density foam core Ash, Caramel or Chestnut
Cover Lifter (Optional)	CoverCradle®, CoverCradle II, Lift 'n Glide®
Steps (Optional)	Everwood® or Polymer Coastal Gray, Espresso or Teak

- Includes water and 3 adults weighing 175 lbs. each.
 Requires a dedicated circuit supplied to the unit at all times. Electrical requirements will vary outside the U.S.
 G.F.C.I. protected sub-panel required in 30amp conversion or 220v mode.
 Export models available in 230v, 50Hz, 1000w heater.

From the makers of

