



An Innovation of King Technology

@ease®

START-UP & BASIC OPERATION TIPS

1

If previously using bromine or biguanides, drain, rinse and refill the hot tub. Otherwise proceed to Step 2.

2

Test the water with FROG® @ease® Test Strips and balance according to the Water Balance Guidelines.

Water Balance Guidelines

pH.....7.2-7.8
 Total alkalinity..... 80-120 ppm
 Calcium Hardness..... 150-250
 Total Dissolved Solids..... <1500
 Free Chlorine 0.5-1.0 ppm

NOTE: Free Chlorine levels are reduced up to 75% when using FROG minerals.



3

Shock the hot tub with FROG® Jump Start® to achieve a start-up level of chlorine.



4

Set the dial on the blue FROG @ease Mineral Cartridge to #4. For the silver FROG @ease SmartChlor Cartridge, use the setting chart.

Setting # on the FROG @ease SmartChlor Cartridge



FROG @ease Setting Chart

Bullfrog Spa Models	Gallons	Setting #
A5L, R5L, STIL5	200-299	1
A6, A6L, STIL7, R6, R6L, X7, X7L	300-399	2
A7, A7L, R8L, R7, R7L, X8, X8L	400-499	3
A9L, A8, A8L, R8	500-600	4

5

Snap the two cartridges into the cartridge holder.



6

Place the holder between the filter cartridges in your Bullfrog Spa.



7

When the FROG @ease SmartChlor Cartridge is empty replace with a new one and offer the old one for recycling if available.

SMARTCHLOR CARTRIDGE LASTS 3-4 WEEKS



8

Shock the hot tub when you replace the FROG @ease SmartChlor cartridge or once a month.